WATERPROOF POCKET-SIZED THERMOMETER

- Includes max/min recording function
- Waterproof to IP66/67

This waterproof thermometer measures temperature over the range of -49.9 to 199.9 °C with a 0.1 °C resolution and features a max/min temperature recording function and at the back of the instrument a discreet °C/°F and reset button.

The unit incorporates a Ø2.5 x 122 mm stainless steel food penetration probe. This waterproof thermometer incorporates the latest microprocessor technology, designed for reliability and ease of use in routine day-to-day catering, food preparation and industrial applications.

Each unit is supplied with a protective probe cover that incorporates a pocket clip and wall-mounting keyhole slot.

OPTIONAL ACCESSORY:

 Protective silicone boot protects from accidental damage (830-275)



Order codeDescription810-275Waterproof thermometer

830-275 Protective silicone boot

| | COMATINE MIN 1967 |
|---------------|---|
| Specification | Waterproof pocket-sized |
| Range | -49.9 to 199.9 °C |
| Resolution | 0.1 °C/°F |
| Accuracy | ±0.5 °C (-9.9 to 99.9 °C) otherwise ±1.5 °C |
| Battery | 3 volt CR2032 lithium coin cell |
| Battery life | 5000 hours |
| Sensor type | Thermistor |
| Display | 8 mm LCD |
| Dimensions | 15 x 26 x 200 mm |
| Weight | 25 grams |

MAX/

AUTO

MAX/

IP66/

[IP66/

WATERPROOF T-SHAPED THERMOMETERS

- Robust & heavy duty, optional longer probe
- Max/min memory & display hold functions

These easy to use, digital T-shaped waterproof thermometers offer IP66/67 protection and incorporate a reduced tip probe that is ideal for heavy duty applications.

Measuring temperature over the range of -49.9 to 149.9 °C with a 0.1 °C resolution, the thermometer will power off automatically after fifteen minutes, maximising battery life.

Each unit is housed in a robust polycarbonate case with a strong, stainless steel, penetration probe. The probe measures \emptyset 5 x 125 mm or 300 mm with a reduced tip (\emptyset 3.5 x 20 mm) to improve response time. The waterproof thermometers feature max/min memory and display hold functions.

| Order code | Description |
|------------|-------------------------|
| 810-285 | T-shaped - 125 mm probe |
| 810-287 | T-shaped - 300 mm probe |



| Waterproof T-shaped |
|----------------------------|
| -49.9 to 149.9 °C |
| 0.1 °C |
| ±1 °C (-19.9 to 119.9 °C) |
| 1.5 volt LR44 - 5000 hours |
| Thermistor |
| 12 mm LCD |
| 30 x 88 x 170/345 mm |
| 50/55 grams |
| |

HOLD